



## **BöttcherFount N-1008**

## **Fountain Solution for Coldset**

BöttcherFount N-1008 is a fountain solution additive for newspaper printing. For all types of coldset presses with spray dampening systems.

- odosage range 2,5-3 %
- very fast start-up and clean plates
- strong plate protection, no scumming after press stop
- or long runs without washing the blanket
- reduced water setting can be reduced by 10-20%
- improved brilliance of the ink
- higher ink density, ink stays on top of the paper, more gloss
- reduced ink consumption
- on strike-through of the ink
- corrosion inhibited, complies with the requirements of FOGRA
- Oph-value (at 2,5%): 4.9 to 5.3 (depending on water hardness)
- reduced build-up of ink on dampening rollers
- of the for soft and hard water
- effective prevention of foam
- increase of conductivity per % input: 490 µS/cm

Before applying BöttcherFount N-1008, the fountain system must be completely emptied and cleaned thoroughly, preferably with Böttcher Pro Slimex.

BöttcherFount N-1008 meets the requirements of the "Corrosion Certificate of Fountain Soultion Additive".







- 200 kg barrel
- 600 kg container
- 1.000 kg container

BöttcherFount N-1008 is classified according to EC-Directive 1999/45/EC – in ist latest version and does not need to be marked. BöttcherFount N-1008 is not a dangerous good in the sense of national and international transport regulations.

All our product information sheets, as well as our contact data you will find on the internet www.boettcher-systems.com.

## Felix Böttcher GmbH & Co. KG

## Headquarter

Stolberger Str. 351 - 353 50933 Cologne, Germany Phone +49 (0) 221 4907 - 1 Fax +49 (0) 221 4907 - 435 koeln@boettcher-systems.com



