



BöttcherFount N-1006

Fountain Solution Additive

BöttcherFount N-1006 is a fountain solution additive with increased conservation for newspaper printing. For all types of presses and dampening units.

Especially recommended for spray dampening units.

- dosage range 2 3 % volume
- fast runoff, therefore less waste
- very stable ink-/ water-balance
- less residual moisture in the paper
- wide dampening range with reduction in water setting
- reduced build-up ink on dampening rollers
- reduced build-up of paper dust and ink on the blanket
- no ink feedback in the dampening solution
- good corrosion protection
- for water hardness 5 to 20° dH (total hardness)
- pH-value 5,0 5,2 (depending on water hardness)
- increased conductivity per % input: 415 µS/cm
- density 1,09 (kg/l)

Before applying BöttcherFount N-1006 B, the fountain system must be completely emptied and cleaned thoroughly, preferably with BöttcherPro Hydroclean.

BöttcherFount N-1006 meets the requirements of the press manufactures "Corrosion Certificate of Fountain Solution Additive", approved by press manufactures.



lote





- 200 kg barrel
- 600 kg container
- 1000 kg container

BöttcherFount N-1006 is classified and marked according to EC-Directive 1999/45/EC - in its latest version. BöttcherFount N-1006 B is not a dangerous good in the sense of national and international transport regulations.

All our product information sheets, as well as our contact data you will find on the internet www.boettcher-systems.com.

Felix Böttcher GmbH & Co. KG

Headquarter

Stolberger Str. 351 - 353 50933 Cologne, Germany Phone +49 (0) 221 4907 - 1 Fax +49 (0) 221 4907 - 435 koeln@boettcher-systems.com



