

# BöttcherPro PRO-TECT Sealer

## Protection coating

---

Oil-based coating that is applied on the printed sheet via the last ,inking unit“ of a commercial sheetfed press. It allows faster turnaround times, faster secondary press pass and print finishing. Used in presses without coating unit.

*Application*

- 
- Used in the last inking unit
  - Avoids drying problems on matt coated paper
  - Provides the printed sheet with an almost invisible protecting layer
  - Starts to dry within an extremely short time
  - Allows faster print finishing thanks to less waiting time for drying
  - Even if the ink layer below the coating isn't completely dry yet, the further steps (for example backside printing, folding, cutting, binding) are possible without the risk that the ink blurs on the print image → Inline-protection for the print image
  - Low gloss, (effect as matt coated paper)
  - Oxidative drying

*Properties*

- 
- Reduced time for print jobs, as faster secondary press pass and less waiting time for print finishing. Good stacking characteristics and reduced ink transfer from one sheet to another
  - Better print quality
  - No yellowing effect!**

*Advantages*





Consumption 0,3 – 1,0 g/m<sup>2</sup>

Note

2,5 kg tin → sale in cartons of eight tins

Package

BöttcherPro PRO-tect Sealer is classified according to EC-Directive 1999/45/ EC - in its latest version and does not need to be marked. BöttcherPro PRO-tect Sealer is not a dangerous good in the sense of national and international transport regulations

Marking

All our product information sheets, as well as our contact data you will find on the internet [www.boettcher-systems.com](http://www.boettcher-systems.com).

### Felix Böttcher GmbH & Co. KG

#### Headquarter

Stolberger Str. 351 - 353  
50933 Cologne, Germany  
Phone +49 (0) 221 4907 - 1  
Fax +49 (0) 221 4907 - 435  
koeln@boettcher-systems.com



[www.boettcher.de/contact](http://www.boettcher.de/contact)

