



VitaFount S

Fountain Solution Additive

VitaFount S is a fountain solution additive for sheet-fed offset and continuous form printing. Applicable particularly in food packaging printing.

- use at a concentration of 2 3 %
- for IPA-reduction to 6 8 %
- very stable ink-/water-balance
- reduced water pick-up of the ink, therefore higher ink densities obtained
- or water hardness 5 20° dH (total hardness) density 1.10 (kg/l)
- pH-value 4.8 5.0 (depending on water hard- suitable for UV and Hybrid inks as well as ness)
- reduced calcium deposits on ink rollers
- corrosion inhibited

- on the minimises build-up of paper dust and ink on the blanket
- suitable for CTP plates
- effective plate protection during press stops
- suitable for copper rollers
- fast start-up and stable printing for long runs (1) increased conductivity per % input: 420 μS/cm

 - special inks containing metallic pigments

Before applying VitaFount S, the fountain system must be completely emptied and cleaned thoroughly, preferably using BöttcherPro Hydroclean.

It is approved by the ISEGA, intended use provided, VitaWash S is therefore appropriate for the appli cation in the food packaging printing.









- 20 kg can
- 200 kg container

VitaFount S is classified according to EC-Directive 199/45/EC - in its latest version - and does not need to be marked.

VitaFount S is not a dangerous good in the sense of national and international transport regulations.

All our product information sheets, as well as our contact data you will find on the internet www.boettcher-systems.com.

Felix Böttcher GmbH & Co. KG

Headquarter

Stolberger Str. 351 - 353 50933 Cologne, Germany Phone +49 (0) 221 4907 - 1 Fax +49 (0) 221 4907 - 435 koeln@boettcher-systems.com



